



TEC MARK 3000 Series

PRODUCT DESCRIPTION

70 My stabilized calendered monomeric vinyl

A perfect glossy face film in addition to high flexibility and conformability makes the product suitable also for non-smooth surfaces

Ecological compatible acrylic adhesive

Easy sign on cutting plotters

Coated with a semi-permanent acrylic pressure sensitive adhesive

Suitable for indoor and outdoor medium-term applications from 3 to 5 years minimum.

CHARACTERISTICS:	Unit	Value	Tolerance	Norm
Face film : calendered monomeric vinyl				
Thickness	mm	0,070	± 10%	ASTM D374
Total thickness	mm	0,100	± 10%	ASTM D374
Liner: one side silicone paper				
Weight	g/m ²	120	± 10	ASTM D646
Adhesion on steel	N/"	10	± 2	AFERA 4001
Dimensional stability	mm	1	max	FINAT FTM 14
Application temperature	°C	10 ÷ 40		
Service temperature	°C	-20 ÷ 50		
Outdoor duration		3-5 years		

SHELF LIFE : Minimum 2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity .

AVAILABLE COLOURS : 39 gloss – 35 mat

STANDARD DIMENSIONS: Log 1220mm x 50m

V.1.1 12/07

COMPANY OPERATING WITH INTERNATIONAL QUALITY SYSTEM VISION 2000



www.kemica.it

20010 Cornaredo (MI) Italy
Via Merendi, 37

Tel. +39.02935301 Fax +39.0293560025